

LIGHT

Forged aluminium wheel.

ROBUST

High-resistance forged alloy.

ECONOMIC

More usable load.



BPW · THE QUALITY FACTOR



PRODUCT OVERVIEW. ECO WHEEL

Forged aluminium wheels for increased economy

5-year guarantee

Without kilometre limit*

KBA APPROVAL
FOR ALL
WHEEL SIZES

Date 01/2011

Wheel size	Recommended tyre size	Surface	Offset (mm)	Half centre distance (mm)	Bolt hole Diameter (mm)	Maximum wheel load (kg)	Weight (kg)	Wheel connection	Key thickness (mm)	Twin assembly	Use	BPW. code no.
22.5 x 11.75	365/70 R22.5; 385/65 R22.5; 385/55 R22.5; 15 R22.5	Brushed	120	-	32	5000	26.2	281/335/10	27	no	Truck & Trailer/semitrailer	02.3511.43.12
					26		26.4					02.3511.44.12
		Highly polished	120	-	32	5000	26.2	281/335/10	27	no	Truck & Trailer/semitrailer	02.3511.45.12
					26		26.4					02.3511.46.12
		Brushed	0	-	32	4500	22	281/335/10	23	no	Trailer/semitrailer	02.3511.47.12
					26		22.2					02.3511.48.12
		Highly polished	0	-	32	4500	22	281/335/10	23	no	Trailer/semitrailer	02.3511.49.12
					26		22.2					02.3511.50.12
22.5 x 9.00	12 R22.5; 12/70 R22.5; 285/60 R22.5; 295/60 R22.5; 305/60 R22.5; 315/60 R22.5; 285/70 R22.5; 295/70 R22.5; 305/70 R22.5; 315/70 R22.5; 285/75 R22.5; 295/75 R22.5; 305/75 R22.5; 315/75 R22.5; 285/80 R22.5; 295/80 R22.5; 305/80 R22.5; 315/80 R22.5	Brushed	153	175	32	4250	25.4	281/335/10	22	yes	Truck & Trailer/semitrailer	02.3511.51.12
					26		25.6					02.3511.52.12
					32		25.4					02.3511.53.12
					26		25.6					02.3511.54.12
		Highly polished	153	175	32	4250	25.4	281/335/10	22	yes	Truck & Trailer/semitrailer	02.3511.55.12
					26		25.6					02.3511.56.12
					32		22.9					02.3511.57.12
					26		23.1					02.3511.58.12
22.5 x 8.25	11 R22.5; 12 R22.5; 265/60 R22.5; 285/60 R22.5; 255/70 R22.5; 265/70 R22.5; 275/70 R22.5; 285/70 R22.5; 295/70 R22.5; 305/70 R22.5; 255/75 R22.5; 265/75 R22.5; 275/75 R22.5; 285/75 R22.5; 295/75 R22.5; 305/75 R22.5; 255/80 R22.5; 265/80 R22.5; 275/80 R22.5; 285/80 R22.5; 295/80 R22.5; 305/80 R22.5	Brushed	145	167	32	3650	22.9	281/335/10	22	yes	Trailer/semitrailer	02.3511.55.12
					26		23.1					02.3511.56.12
					32		22.9					02.3511.57.12
					26		23.1					02.3511.58.12
		Highly polished	145	167	32	3650	22.9	281/335/10	22	yes	Trailer/semitrailer	02.3511.59.12
					26		23.1					02.3511.60.12
					32		22.9					02.3511.57.12
					26		23.1					02.3511.58.12
17.5 x 6.75	9.5 R17.5; 10 R17.5; 205/75 R17.5; 215/75 R17.5; 225/75 R17.5; 235/75 R17.5; 245/70 R17.5; 245/75 R17.5	Brushed	117	137	26	3000	14.8	176/225/10	20	yes	Trailer/semitrailer	02.3511.59.12
					26		14.8					02.3511.60.12
		Highly polished	117	137	26	3000	14.8	176/225/10	20	yes	Trailer/semitrailer	02.3511.59.12
					26		14.8					02.3511.60.12

Nuts for wheel fastening (wheel nuts with corrosion-resistant Dacromet coating)

Nut for aluminium + steel (silver)		M 22 x 1.5/27 mm high	26	05.260.54.10.0
Shaft nut, short (silver)	Individual tyres	M 22 x 1.5/39 mm high	32	05.260.54.21.1
Shaft nut, long (silver)	Twin tyres	M 22 x 1.5/62 mm high	32	05.260.54.14.1

Nuts for wheel fastening (nuts with inched thread must be used for Scania/Volvo)

Shaft nut, short, Scania	Individual tyres	7/8", 11 BSF	32	02.5219.39.10
Shaft nut, long, Scania	Twin tyres	7/8", 11 BSF	32	02.5219.40.10
Shaft nut, short, Volvo	Individual tyres	7/8", 14 UNF	32	02.5219.41.10
Shaft nut, long, Volvo	Twin tyres	7/8", 14 UNF	32	02.5219.42.10

* according to warranty conditions

You can find further information at www.bpw.de

BPW Bergische Achsen Kommanditgesellschaft

P.O. Box 1280 · D-51656 Wiehl · Phone +49 2262 78-0 · info@bpw.de · www.bpw.de